

Godrej

GODREJ LIGHT COMMERCIAL FIX SPEED CASSETTE RANGE



COOLING
TECHNOLOGY*



ANTI-CORROSIVE
BLUE FINS*

5
YEAR

COMPRESSOR
WARRANTY*

RATED
No.1
IN AFTER-SALES
SERVICE.*

Godrej smart
care
PROFESSIONALS AT YOUR CALL

Toll Free : 1800 209 5511
Message "Hi" on
WhatsApp on
93216 65511

- 24 X 7 CALL CENTRE,
- VISIT UP TO 9 PM,
- WEEKEND SERVICE



Recyclable material. Dispose
responsibly.
To know more visit:
<https://www.godrej.com/green-think>



SCAN HERE TO
KNOW MORE

www.godrej.com/appliances

f GodrejAppliances

X GodrejAppliance

Instagram GodrejAppliance

*Conditions apply.*TnC Apply: http://bit.ly/GATnC_ *Features vary by models.*Based on independent consumer survey conducted in Dec'23-Jan'24. For details, visit http://bit.ly/GATnC_

ECO FRIENDLY TECHNOLOGIES

GODREJ SPECIFICATION SHEET

TECHNICAL SPECIFICATIONS	FIX SPEED CASSETTE ACs	
	AC 2T CFC 24FTC3 4YA	AC 3T CFC 36FTC2 4YA
RATED VOLTAGE / FREQUENCY / PHASE	230 V / 50 Hz / 1 ph	230 V / 50 Hz / 1 ph
TONNAGE CLASSIFICATION	2 Tr.	3 Tr.
RATED COOLING CAPACITY (Watts)	6200	10600
POWER INPUT IN WATTS	1591	3370
ISEER (STAR RATING)	3.9 (3 Star)	3.15 (2 Star)
ELECTRICITY CONSUMPTION (1600 HOURS) UNITS PER YEAR	1231.6	2608.74
RATED CURRENT (AMP)	7.3	15.4
AIR FLOW VOLUME (DRY CFM/DRY CMH)	795 / 1350	1236 / 2100
COOLING DIRECTIONS	360° COOLING	360° COOLING
NOISE LEVEL INDOOR (HIGH/ MEDIUM / LOW) in dB(A)	46 / 44 / 43	52 / 50 / 48
MODES	COOL/AUTO/DRY/FAN/TURBO	COOL/AUTO/DRY/FAN/TURBO
HORIZONTAL LOUVER	AUTOMATIC	AUTOMATIC
MEMORY FUNCTION	YES	YES
SELF CLEAN	YES	YES
TIMER	YES	YES
ANTI FREEZE	YES	YES
DISPLAY IN IDU	HIDDEN DISPLAY	HIDDEN DISPLAY
CLOCK	YES	YES
FILTER CONFIGURATION	ANTI DUST FILTER	ANTI DUST FILTER
EVAPORATOR FINS	HYDROPHILIC BLUE FINS	HYDROPHILIC BLUE FINS
CONDENSER FINS	COPPER CONDENSER WITH ANTI CORROSIVE BLUE FINS	COPPER CONDENSER WITH ANTI CORROSIVE BLUE FINS
EXPANSION DEVICE IN ODU	CAPILLARY	CAPILLARY
NET IDU DIMENSION (W X H X D) cm	85.8 x 85.4 x 24.5	85.8 x 85.4 x 29.0
GROSS IDU DIMENSION (W X H X D) cm	95.0 x 95.0 x 32.8	95.0 x 95.0 x 37.3
INPUT POWER SUPPLY	OUTDOOR UNIT	OUTDOOR UNIT
NET WEIGHT IDU (kg)	24	26
GROSS WEIGHT IDU (kg)	30.5	32
NET ODU DIMENSION (W X H X D) cm	85.0 x 68.4 x 31.0	92.8 x 75.5 x 32.8
GROSS ODU DIMENSION (W X H X D) cm	103.2 x 75.5 x 45.0	107.5 x 82.0 x 45.0
NOISE LEVEL OUTDOOR in dB(A)	60	60
NET WEIGHT ODU (kg)	44	59.5
GROSS WEIGHT ODU (kg)	48.5	64
COMPRESSOR TYPE	ROTARY FS	ROTARY FS
COMPRESSOR WARRANTY	5 YEAR	5 YEAR
REFRIGERANT	R32	R32
MAX AMBIENT TEMP (COOLING)°C	48	48
SUCTION TUBE SIZE OUTER DIAMETER INCHES (mm)	5/8"	5/8"
LIQUID TUBE SIZE OUTER DIAMETER INCHES (mm)	1/4"	3/8"
MAX PIPING CAPABILITY TOTAL (m)	15	15
MAX PIPING CAPABILITY VERTICAL (m)	10	10
REFRIGERANT ADDITIONAL CHARGE BEYOND 4m (g/m)	20	20